



#0747 Blue Tint

A thermoplastic Blue Tint coating that can be applied onto various gauges of PET base film. #0747 was developed as an alternative to DYED PET film. Typically used as a backside tint, #0747 is paired with various silicone release coatings for a variety of end uses.

Typical Properties

Typical Values

CROSS-HATCH ADHESION	NO REMOVAL
COLOR	LIGHT BLUE TINT / INDUSTRIAL MATCH
COATING WARRANTY	12 MONTHS FROM DATE OF MANUFACTURE

Advantages

- Smooth uniform surface
- Excellent adhesion to base film
- Excellent winding characteristics

Applications

- Backside Tint of coated 2-side products
- Mainly for Product ID purposes



The above are typical values that reflect product performance and are not intended to be used a specification. For product specifications, please contact our quality department

NORFILM™ Film Selection Guide*

Film	Gauge	Market	Applications	Key Properties
Polyester (PET)	92-1400	Label	Roll Label, Overlaminates, Beverage, Pharmaceutical, Toiletries, Health & Beauty	High Tensile and Tear Resistance Excellent Smoothness High Clarity Gauge Control Temperature Resistance Recyclable Back Side Printable Mechanically Stable Spliceable
		Decal Graphic	Transfer Lettering, Window Graphics	
		Industrial	Solar, Gaskets, Nameplate, Automotive, Construction, Composites, Free Adhesives	
		Tape	One/Two Side, Transfer	
		Medical	Transdermal, Hydrogels, Wound Care, EKG, Hygiene	
Polystyrene (PS)	750-1000	Medical	Hydrogels, Wound Care, EKG	Thermoformable Good Stiffness Back Side Printable
		Label	Piggyback	
Polyvinyl Chloride (PVC)	800-1000	Medical	Transdermal, Hydrogels, EKG	Thermoformable
Polyethylene (PE)	100-2300	Tape	One/Two Side, Transfer	Tear Resistance Conformable High Yield
		Medical	Wound Care, Hygiene	
		Industrial	Construction Gasket, Automotive	

*Represent typical performance properties and should not be used for specification purposes

Contact your Saint-Gobain Performance Plastics representative for more information.



Saint-Gobain Performance Plastics — The Americas

717 Plantation Street
Worcester, MA 01605
Tel: (508) 852-3072
Fax: (508) 852-3759
www.plastics.saint-gobain.com
email:norfilm@saint-gobain.com

Saint-Gobain Performance Plastics — Europe

Bay 3 Transpennine Industrial Estate
Gorrels Way, Rochdale, OL11 2PX
United Kingdom
Tel: +44 (0) 1706 746900
Fax: +44 (0) 1706 746991
email: aff.uk@saint-gobain.com

Saint-Gobain Performance Plastics — Asia

7 Floor Bund Center
222 Yan'an Road East
Shanghai 200002, China
Tel: (86) 21-63617753/63618016
email: industrialfilms.asia@saint-gobain.com

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s).

SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.