



FluoroSilicone Release Liners

Saint-Gobain offers coatings of fluorinated polysiloxane developed specifically for silicone adhesive applications. We utilize state-of-the-art coating systems to apply specialty formulations on various base films to provide competitively priced, high-quality static dissipative film.

| | |
|----------------|------------------------------------|
| Product | FluoroSilicone |
| Coatings | 9011 |
| Substrates | Standard and specialty treated PET |
| Release Values | <75 grams/inch |

Saint-Gobain is a leader in manufacturing surface coatings in both standard and custom formulations. Flexible engineering and manufacturing capabilities enable us to design products for a diverse range of applications and disciplines.

Features/Benefits

- **FDA:** Drug Master File listed for medical applications
- **Options:** Multiple coatings and multiple substrates available
- **Wide roll** production delivered in narrow roll configurations
- **Clarity:** Very clear and smooth coatings

Applications

- High temperature tapes
- Medical tapes
- Specialty labels and tapes



NORFILM™ Film Selection Guide*

| Film | Gauge | Market | Applications | Key Properties |
|---------------------------------|----------|---------------|--|---|
| Polyester (PET) | 92-1400 | Label | Roll Label, Overlaminates, Beverage, Pharmaceutical, Toiletries, Health & Beauty | High Tensile and Tear Resistance Excellent Smoothness High Clarity Gauge Control Temperature Resistance Recyclable Back Side Printable Mechanically Stable Spliceable |
| | | Decal Graphic | Transfer Lettering, Window Graphics | |
| | | Industrial | Solar, Gaskets, Nameplate, Automotive, Construction, Composites, Free Adhesives | |
| | | Tape | One/Two Side, Transfer | |
| | | Medical | Transdermal, Hydrogels, Wound Care, EKG, Hygiene | |
| Polystyrene (PS) | 750-1000 | Medical | Hydrogels, Wound Care, EKG | Thermoformable Good Stiffness Back Side Printable |
| | | Label | Piggyback | |
| Polyvinyl Chloride (PVC) | 800-1000 | Medical | Transdermal, Hydrogels, EKG | Thermoformable |
| Polyethylene (PE) | 100-2300 | Tape | One/Two Side, Transfer | Tear Resistance Conformable High Yield |
| | | Medical | Wound Care, Hygiene | |
| | | Industrial | Construction Gasket, Automotive | |

*Represents typical performance properties and should not be used for specification purposes
Contact your Saint-Gobain Performance Plastics representative for more information.



Saint-Gobain Performance Plastics — The Americas

717 Plantation Street
Worcester, MA 01605
Tel: (508) 852-3072
Fax: (508) 852-3759
www.plastics.saint-gobain.com
email.norfilm@saint-gobain.com

Saint-Gobain Performance Plastics — Europe

Bay 3 Transpennine Industrial Estate
Gorrels Way, Rochdale, OL11 2PX
United Kingdom
Tel: +44 (0) 1706 746900
Fax: +44 (0) 1706 746991
email: aff.uk@saint-gobain.com

Saint-Gobain Performance Plastics — Asia

7 Floor Bund Center
222 Yan'an Road East
Shanghai 200002, China
Tel: (86) 21-63617753/63618016
email: industrialfilms.asia@saint-gobain.com

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s).

SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.